



Driver identification Keypad

TC-261048



Introduction

The ***TC-261048 keypad*** is used for Driver ID input within the scope of the Driver Authentication feature of the tracking unit. This method is more flexible than the IButton key option as the driver no longer needs to carry the IButton key and it prevents problems caused by the loss of IButton keys.

The user enters a Driver ID of up to 14 digits in length (1-5 followed by star (*)). The keypad transfers the Driver ID to the tracking unit, via the IButton interface. The tracking unit activates the Driver Authentication process, sends a driver ID message to the control center and / or deactivates the vehicle immobilizer according to the feature's programmable parameters.

Compatibility

The **TC-261048 keypad** supports tracking devices that are supporting 1-wire protocols. Amongst them are: Teltonika, Queclink, Digital Matter.

Main Capabilities

The **TC-261048 keypad** supports the following main capabilities:

- Driver ID of up to 14 digits in length (1-5 followed by star (*)).
- Background light allows convenient operation at night.
- Audible indication for dialing process.
- Vocal indication when the Driver ID is transmitted.
- Transmits the Driver ID to the tracking unit via 1-Wire® iButton operation.
- Average minimum power consumption.

The keypad Interfaces

The following table presents the **TC-261048 keypad** interfaces. For each interface the wire, functionality and recommended connection is described.

Wire Name	Wire Color	Interface	Functionality	Connection
Power	Yellow		Powering the keyboard	Vehicle power supply
Ground	Brown		Powering the keyboard	Vehicle ground
Buzzer	Green	Active Low	Control of vocal	Tracking unit output
Data	White	1-Wire protocol	Communication with the tracking device	Tracking unit dallas interface

Electrical Specifications

Parameter	Description
Supply voltage	8 V - 36 V
Current consumption	< 5 mA typical
Protection	The device will not be damaged if the power supply wires are connected with inverted polarity
Communication protocol	1-Wire® protocol
Communication distance	10 meters maximum

Physical and Environmental Specifications

Parameter	Description
Dimension	28mm x 48mm x 13mm
Working temperature	-20°C to 70°C
Wire length	150 cm

For further information contact us on
info@trackinghardware.co.uk