



# Driver identification Keypad

## *DC-51145*



### Introduction

The **DC-51145 Keypad** is used for Driver ID input within the scope of the Driver Authentication feature of the tracking unit. This method is more flexible than the IButton key option as the driver no longer needs to carry the IButton key and it prevents problems caused by the loss of IButton keys.

The user enters a Driver ID of up to 14 digits in length (0-9 followed by star (\*)). The keypad transfers the Driver ID to the tracking unit, via the IButton interface. The tracking unit activates the Driver Authentication process, sends a driver ID message to the control center and / or deactivates the vehicle immobilizer according to the feature's programmable parameters.

## Compatibility

The **DC-51145 Keypad** supports tracking devices that are supporting 1-wire protocols. Amongst them are: Teltonika, Queclink, Digital Matter.

## Main Capabilities

The **DC-51145 Keypad** supports the following main capabilities:

- Driver ID of up to 14 digits in length (0-9 followed by star (\*)).
- Background light allows convenient operation at night.
- Audible indication for dialing process.
- Vocal indication when the Driver ID is transmitted.
- Transmits the Driver ID to the tracking unit via 1-Wire® iButton operation.
- Average minimum power consumption.
- IP64

## The keypad Interfaces

The following table presents the **DC-51145 Keypad** interfaces. For each interface the wire, functionality and recommended connection is described.

| Wire Name | Wire Color | Interface       | Functionality                          | Connection                     |
|-----------|------------|-----------------|--|--------------------------------|
| Power     | Yellow     |                 | Powering the keyboard                  | Vehicle power supply           |
| Ground    | Brown      |                 | Powering the keyboard                  | Vehicle ground                 |
| Buzzer    | Green      | Active Low      | Control of vocal                       | Tracking unit output           |
| Data      | White      | 1-Wire protocol | Communication with the tracking device | Tracking unit dallas interface |

## Electrical Specifications

| Parameter              | Description   |
|------------------------|---|
| Supply voltage         | 8 V - 36 V  |
| Current consumption    | < 5 mA typical  |
| Protection             | The device will not be damaged if the power supply wires are connected with inverted polarity |
| Communication protocol | 1-Wire® protocol  |
| Communication distance | 10 meters maximum   |

## Physical and Environmental Specifications

| Parameter           | Description        |
|---------------------|--------------------|
| Dimension           | 73mm x 46mm x 17mm |
| Working temperature | -20°C to 70°C      |
| Wire length         | 150 cm             |

**For further information contact us on**  
[info@trackinghardware.co.uk](mailto:info@trackinghardware.co.uk)